

# GRAFFIPRO AQ

LONG LASTING PROTECTION FOR MOST TYPES OF SURFACE AGAINST GRAFFITI AND THE ADHERENCE OF STICKERS & POSTERS

GRAFFIPRO AQ is a silicone free complex of synthetic resins which gives a colourless protective film that resists water and bad weather. GRAFFIPRO AQ can be applied on most types of surface including concrete, cement mixtures, stone, brick, block, resistant paints etc ...

GRAFFIPRO AQ prevents the pigments and solvents, contained in spray paint, forming a permanence as well as the adhesion of stickers and posters. It also has the advantage of protecting the treated surfaces against the solvents held within the paint or adhesive.

GRAFFIPRO AQ maintains its function for up to 5 years, however, a pre-test must always precede the use of the product.

Appearance.....	Viscous liquid
Colour.....	Off-white
Density.....	1.00 - 0.02
Solubility.....	Total in water
Flammability.....	Non flammable
pH.....	8.5

1. Before the application of GRAFFIPRO AQ, surfaces must be clean and free of dust.
2. We recommended mixing/stirring the product prior to application.
3. GRAFFIPRO AQ is applied by brush or roller. Apply at least two crossed layers.
4. Do not apply on hot surfaces or at temperatures below 5 ° C
5. Effective protection of the surface is obtained after a polymerisation time of about 48 hours.

## GRAFFITI CLEANING PROCESS

1. The cleaning should be carried out with a hot alkaline water solution.
2. If, after cleaning, some graffiti persists use GRAFFINET DC cleaner.
3. After cleaning it is necessary to apply one coat of GRAFFIPRO AQ to the cleaned area.
4. Posters and most stickers should come off without intervention.

The equipment used to implement the GRAFFIPRO AQ is cleaned with water.  
GRAFFIPRO AQ should be protected from frost.

Coverage for porous surfaces: 4 - 6m<sup>2</sup> per litre  
 Coverage for smooth, non-porous surfaces: 6 -12m<sup>2</sup> per litre